

# LUBRICANTS & COOLANTS CATALOGUE




# WÜRTH INSIGHT



WÜRTH Headquarters – Künzelsau, Germany

- More than 1,00,000 product lines
- Total employees: > 79,000
- Over 3.9 million customers worldwide
- 2020 sales: EUR 14.4 billion
- Standard & Poor's rating: A Stable
- Over 400 companies in more than 80 countries



**We make connections** worldwide

## WUERTH INDIA

**Central Support Centre – Mumbai**

**Regional Support Centre – Chennai | Delhi | Kolkata**

**Over 852 employees working in across 35 locations to serve the customers**



Our product range includes products for Automotive Technology, Service Maintenance, Chemicals, Paints, Engine Oils, Adhesives, Abrasives, Cutting Devices, Fasteners, Furniture and Construction Fittings, Dowel Technology, Industrial Safety and much more.

## BUSINESS AREAS



**AUTO**

**MOTORBIKE**

**CARGO**

**METAL**

**CONSTRUCTION**

**PAINTS**

## ENGINE OIL

### ENGINE OIL 0W - 40

Fully Synthetic



### API SN/CF

#### Fully Synthetic SAE 0W - 40

Wuerth 0W - 40 ACEA A5 B5 is a full synthetic, full SAPS, super high performance engine oil which meets the ACEA A5/B5, BMW Long Life 01, Porsche A40, VW 502 00/ 505 00 and MB 229.3 and 229.5 specifications. It combines the latest developments in oil formulation and additive technology to provide a lubricating oil with the highest level of protection, whilst promoting fuel efficiency and lowering emissions in modern low friction engines.

Art. No.	Contents
0897104401	1 L
0897104402	4 L

### ENGINE OIL 5W - 40

Synthetic



### API SM/CF

#### High Technology Synthetic Engine Oil

Wuerth 5W - 40 meets API SM/CF, ACEA A3/B4-10, VW 502 00/505 00, MB 229.3, BMW Long Life 01, Porsche A40, Renault RN0700 and RN0710 Specifications and is a premium synthetic oil that provides long engine life for gasoline and diesel engines.

#### Benefits

- Enhanced wear protection
- Enhanced Engine Cleanliness and sludge protection
- Enhanced cold start up performance
- Enhanced high temperature protection

Art. No.	Contents
0897102401	1 L
0897102404	3.5 L
0897102406	4 L
0897102409	55 L
0897102405	210 L

## ENGINE OIL

### ENGINE OIL 5W - 30

Synthetic



### API SM/CF

**Ultra premium synthetic engine oil for new generation petrol and diesel engine**

Wuerth 5W - 30 meets API SM/CF, ACEA A3/134-10, VW 502 00/505 00, MB 229.31 and 229.51, BMW Long Life 04, Porsche C30, Ford WSS-M2C946-A Specifications and is a high performance synthetic oil that provides long engine life for gasoline and diesel engines.

#### Benefits

- Excellent oxidation stability to reduce engine deposits and sludge build up and help maintain engine cleanliness
- Enhanced low temperature capabilities for outstanding cold weather starting
- Enhanced wear protection
- Enhanced high temperature protection

Art. No.	Contents
0897105508	3.5 L
0897105503	55 L
0897105505	210 L

### ENGINE OIL 20W - 50



### API SG/CD

**New generation all season engine oil for passenger vehicles.**

- Specially formulated for Lubrication of naturally aspirated gasoline/petrol engines.
- Offers complete wear protection to moving components in all climatic conditions and even during cold start.
- Keeps engine clean like new engine.

#### Instructions

Recommended Engine lubrication of Maruti, Tata Motors, Mahindra, Hyundai, Ford, Honda, General Motors & Mitsubishi passenger vehicles.

Art. No.	Contents
5869120501	1 L
5869120507	3 L
5869120504	55 L
5869120505	210 L

## ENGINE OIL

### ENGINE OIL 15W - 40

Diesel



### CF4

**Diesel Engine Oil for Passenger Vehicles**

- Engine oil specially formulated from selective base oils and additive packages to meet the lubrication requirements of Diesel Passenger Vehicles. The Multi-grade property ensures that the oil can be used for all climatic conditions. Designed for lubrication of vehicles with Naturally Aspirated or Turbocharged diesel engines both in city, on and off highway roads. The Anti-wear property ensures reduction in engine wear, thus prolonging the life of the engine. The oil has good detergent & dispersant property which keeps the engine parts clean.
- Recommended for engine lubrication of vehicles of TATA Motors, Mahindra, Ford, Honda, General Motors, Hyundai, Mitsubishi SUVs, MUVs and Commercial vehicles. Also suitable for engine lubrication of all Tractors.

Grade : CF4	
Art. No.	Contents
0897154001	1 L
0897154705	7.5 L
0897154015	15 L
0897154055	55 L
0897154210	210 L

### ENGINE OIL 15W - 40

Diesel



### CH4

**High Performance diesel engine oil for new generation passenger vehicles**

- High performance engine oil specially formulated from selective base oils and additive packages to meet the lubrication requirements of all the new generation Diesel Passenger Vehicles. The Multi-grade property ensures that the oil can be used for all climatic conditions. Designed for lubrication of vehicles with Naturally Aspirated or Turbocharged diesel engines both in city, on and off high-way roads. The excellent anti-wear property ensures reduction in engine wear, thus prolonging the life of the engine. The oil has very good detergent & dispersant property which keeps the engine parts clean. Excellent control on oil thickening.
- Recommended for engine lubrication of vehicles of TATA Motors, Mahindra, Ford, Honda, General Motors, Hyundai, Mitsubishi SUVs, MUVs and Commercial vehicles. Also suitable for engine lubrication of all Tractors.

Grade : CH4			
Art. No.	Contents	Art. No.	Contents
5869115411	1 L	5869115408	15 L
5869115403	4 L	5869115414	55 L
5869115412	5 L	5869115415	210 L
5869115407	7.5 L		

## ENGINE OIL

### ENGINE OIL 15W - 40

Diesel



### CI4

**High Performance diesel engine oil for new generation passenger vehicles**

- Diesel engine oil blended using high performance base oils and additive packages to meet the lubrication requirements of all the new generation Diesel Passenger Vehicles. The Multi-grade property ensures that the oil can be used for all climatic conditions. Designed for lubrication of vehicles with Naturally Aspirated, Turbocharged or EGR fitted diesel engines for both in city, on and off highway roads. The superior anti-wear property ensures reduction in engine wear, thus prolonging the life of the engine. The oil has very good detergent & dispersant property which keeps the engine parts clean. Excellent control on oil thickening. Minimizes oil consumption.
- Recommended for engine lubrication of vehicles of TATA Motors, Mahindra, Ford, Honda, General Motors, Hyundai, Mitsubishi SUVs, MUVs and Commercial vehicles. Also suitable for engine lubrication of all Tractors.

Grade : CI4	
Art. No.	Contents
0897154107	7.5 L
0897154115	15 L
0897154155	55 L
0897154205	210 L

### ENGINE OIL 20W - 40

Diesel



### API CF4

**High performance diesel engine oil for lubrication of old engines**

- Engine oil specially formulated from selective base oils and additive packages to meet the lubrication requirements of Diesel Passenger Vehicles.
- The Multi-grade property ensures that the oil can be used for all climatic conditions.
- Designed for lubrication of vehicles with Naturally Aspirated or Turbo-charged diesel engines both in city, on and Off highway roads.
- The Anti-wear property ensures reduction in engine wear, thus prolonging the life of the engine.
- The oil has good detergent & dispersant property which keeps the engine parts clean.
- Engine lubrication of vehicles of TATA Motors, Mahindra, Ford, Honda, General Motors, Hyundai, Mitsubishi SUVs, MUVs and Commercial vehicles. Also suitable for engine lubrication of all Tractors.

Art. No.	Contents
0897120407	55 L
0897120406	210 L



## ENGINE OIL

### ENGINE OIL 10W - 40

Synthetic



### API SL/CF

**Ultra premium synthetic engine oil for new generation petrol & diesel engine**

- Uniquely designed molecules of engine oil keeps engine running like new even in demanding & arduous operating conditions
- Outstanding wear protection
- Excellent low temperature characteristics
- Exceptional high temperature performance
- Outstanding engine cleanliness
- Meets API SL/CF, ACEA A3/B3-10, VW/501 00/505 00, MB 229.1 specifications
- Offers improved fuel economy and emission reduction besides good cold start.

Art. No.	Contents
0897110411	1 L
0897110413	3 L
0897110414	3.5 L
0897110412	4 L
0897110408	55 L
0897110410	210 L



## ENGINE OIL - MOTORCYCLE

### ENGINE OIL 20W - 40

Four Stroke Motorcycle Engine Oil



### API SJ/JASO MA II

- A unique engine oil designed from a combination of high quality mineral base stocks with high performance additives to exceed the highest performance requirements of crankcase and gear lubrication in 4-stroke-motorcycles.
- Exceeds the requirements of JASO MA2.
- Recommended for lubrication of all new generation 4-stroke-motorcycles of Hero, Bajaj Auto, TVS Motors, Suzuki, Honda, Yamaha, Mahindra, LML etc.
- Offers excellent protection as it does not deteriorate even in high operating temperatures.
- Advanced Clutch-Lok Technology ensures improved clutch performance enhancing drive feel.
- Minimizes oil consumption. Balanced product design helps retaining its viscosity for longer time. Ensures protection of engine and transmission components.

Art. No.	Contents
5869120509	900 ml
5869120511	1 L

### ENGINE OIL 20W - 40

Four Stroke Motorcycle Engine Oil



### API SL/JASO MA II

**Premium lubricant for new generation four stroke motorcycles.**

- A premium mineral oil exceeding the requirements of most stringent API - SL service class & meets JASO MA II specification.
- Specially formulated to keep the engine and gearbox clean.
- Keeps engine clean like new engine.
- Offers smooth gear shift and boosts engine performance.
- Recommended for lubrication of Hero, Honda, Bajaj, TVS, Kawasaki and Royal Enfield motorcycles.

Art. No.	Contents
5869120401	1 L
5869120404	55 L





## ENGINE OIL - MOTORCYCLE

### ENGINE OIL 20W - 50

Four Stroke Motorcycle Engine Oil



### API SL/JASO MA II

- Würth 4 T Engine Oil - SAE 20W-50 is a unique engine oil designed from a combination of high quality mineral base stocks with high performance additives to exceed the highest performance requirement of crankcase and gear lubrication in 4-stroke-motorcycles. Exceeds the requirements of JASO MA2.
- Recommended for lubrication of all new generation four stroke motorcycles from Hero, Bajaj Auto, TVS Motors, Suzuki, Honda, Yamaha, Mahindra, LML etc.
- Advanced Clutch- Lok Technology ensures improved clutch performance enhancing drive feel. Minimizes oil consumption.
- Balanced product design aids in retaining its viscosity for longer time. Ensures protection of engine and transmission components.

Art. No.	Contents
5869130511	1 L

### ENGINE OIL 15W - 50

Four Stroke Motorcycle Engine Oil



### API SJ/JASO MA II

**Premium engine oil designed for Royal Enfield 4-stroke motorcycle. Uniquely designed molecules of engine oil keeps engine running like new even in demanding & arduous operating conditions.**

- Würth Premium 15W - 50 4T is a unique engine oil designed from a combination of synthetic and mineral base stocks with high performance additives to exceed the highest performance requirement of crankcase and gear lubrication. Exceeds the requirements of JASO MA2.
- Recommended for lubrication of entire range of Royal Enfield motorcycles. It is also recommended for use in all new generation four stroke motorcycles from Hero, Bajaj Auto, TVS Motors, Suzuki, Honda, Yamaha, Mahindra, LML etc.
- Offers excellent protection as it does not deteriorate even in high operating temperatures.

Art. No.	Contents
0897110525	2.5 L
0897115501	3 L
0897115500	55 L
0897115505	210 L



## ENGINE OIL - MOTORCYCLE

### ENGINE OIL 10W - 30

Four Stroke Motorcycle Engine Oil



### API SL/JASO MA II

- Wuerth 4 T Engine Oil -SAE 10W-30 is a unique engine oil based on synthetic technology with high performance additives to exceed the highest performance requirements of crankcase and gear lubrication in 4-stroke-motorcycles. Exceeds the requirements of JASO MA2.
- Recommended for lubrication of all new generation 4-stroke-motorcycles of Hero, Bajaj Auto, TVS Motors, Suzuki, Honda, Yamaha, Mahindra, LML etc.
- Offers excellent protection as it does not deteriorate even in high operating temperatures.
- Advanced Clutch-Lok Technology ensures improved clutch performance enhancing drive feel. Minimizes oil consumption. Balanced product design helps retaining its viscosity for longer time. Ensures protection of engine and transmission components.

Art. No.	Contents
5869120090	900 ml
0897999001	55 L

### ENGINE OIL 10W - 30

Four Stroke Motorcycle Engine Oil



### API SL/JASO MB

**Premium lubricant for new generation four stroke scooters.**

- This is a latest generation engine oil formulated with premium base stock and suitable additive package for scooters with 4 stroke engines. Suitable for both water and air cooled engines, withstands severe engine operation.
- Specially designed to give the Scooter a greater control through easy acceleration and more enjoyable ride, and ensuring reduced noise and vibration.
- The high quality base oil helps forming an oily film which adheres tenaciously to metal surfaces even when the engine has been standing for some time, thus ensuring easy starting and greatly reducing wear even under high load conditions.

Art. No.	Contents
586912060	800 ml



## ENGINE OIL - MOTORCYCLE

### ENGINE OIL 10W - 40

Four Stroke Motorcycle Engine Oil

### API SN/JASO MA II

**A top of the line four stroke motorcycle engine oil to meet the stringent demands of high performance motorcycles.**

- The engine oil is specially formulated using synthetic base stocks and advanced additive technology to provide outstanding engine cleanliness, wear protection and unsurpassed performance during severe operating conditions.
- Maximizes power output because of better engine performance. Significantly reduces fuel consumption.
- Advanced Clutch-Lok Technology ensures improved clutch performance enhancing drive feel.
- The G-Protek formula ensures excellent wear protection for transmissions. High evaporative stability ensures lower oil consumption.



Art. No.	Contents
0897110511	1 L

## GEAR OIL

### GEAR OIL SAE 80W - 90



### API GL - 4

A high quality gear oil meeting lubrication requirements of passenger cars and commercial vehicles.

The oil is suitable for use in transmission and axle lubrication in passenger cars, commercial vehicle, tractors etc.,

Art. No.	Contents
0897180900	500 ml
0897180901	1 L
0897180906	55 L
0897180905	210 L

### GEAR OIL SAE 85W - 140



### API GL - 5

**Gear oil exceeding highest performance requirements even in sever operating conditions.**

#### Benefits:

- Ultimate gear protection under extreme loads.
- Superior performance even in shock load conditions

Art. No.	Contents
0897185146	55 L
0897185140	210 L

## HYDRAULIC OIL



**HLP 46**  
**HLP 68**

Wurth HLP Hydraulic oil are blended from selective base oils and premium anti wear additives to meet stringent operational conditions of Hydraulic Systems.

Exceeds requirements of ISO – LHM, DIN 51524 teil 2 HLP.

Recommended for use in all type of hydraulic systems operating under moderate pressure (as indicated by the manufacturer) and temperatures.

It is recommended for use in all hydrodynamic power transmission machinery, in hydraulic controls and hydro static systems widely used in all fields of technology such as Transport, Construction and Mining, Chemical, Metallurgical machinery, Machine tools, Marine etc.

Art. No.	0897 646 021	0897 668 021
P. Qty.	1	1
Contents	210 L	210 L
ISO-VG grade	46	68
Approved for hydraulic oils	DIN 51524-2	DIN 51524-2

## BRAKE FLUID - DOT 3 & 4



### Brake Fluid for disc and drum brake systems

- Recommended for all passengers, sports commercial vehicle brake systems requiring products meeting
- BIS8654-Type II, FMVSS 116 DOT 3 and SAEJ 1704 specifications.
- Product enjoys certification to these specifications from ARAI.
- Outstanding corrosion protection for iron and base metals.
- Excellent gas block resistance at high temperature and fluidity at low temperature (-400C) ensures sensitive and safe braking performance

#### DOT 3

Art. No.	Contents
0892008182	250 ml
0892008181	500 ml

#### DOT 4

Art. No.	Contents
0892008191	250 ml
0892008190	500 ml

## RADIATOR COOLANT



**Anti-Corrosive, long life coolant suitable for the protection of cooling systems of all petrol engines and heavy and light-duty diesel engines operating in on-road & off-road or stationary conditions.**

- Prevents boiling of cooling water.
- Increases the cooling system efficiency.
- Improves vehicle performance.
- Can be used for all types of vehicle (Japanese, American, European and Korean).
- Does not damage rubber seals.
- Thick consistency – does not precipitate.
- Mixes evenly with water.
- Increases the life of the engine.
- Mixing ratio 1:2 parts of water.

### Radiator Coolant - WPSC

Art. No.	Colour	Contents
0893601601	Green	1 L
0893601602	Blue	1 L
0893601603	Violet	1 L
0893601604	Red	1 L



### Radiator Coolant - WSC

Art. No.	Colour	Contents
0892501501	Green	1 L
0892501504	Green	3 L
0892501505	Green	5 L
0893556330	Green	30 L
5997609499	Red	30 L
5997609498	Red	210 L



### Premium Anti - Freeze Coolant

Wurth Premium Concentrate Antifreeze/Coolant is the ideal solution to help your engine last longer. Fortified with specially formulated additive package for extended life, corrosion protection and helps keep your cooling system running more efficiently.

Wurth Premium coolant has been formulated using Inorganic Acid Technology (IOAT) intended for long life of coolant.

Art. No.	Colour	Contents
0893556350	Green	500 ml
0893556385	Red	5 L
0893557210	Green	210 L
0893558210	Blue	210 L



# WUERTH OIL RECOMMENDATION

MAHINDRA			
Model	Sump Size	Make	Recommendation
Balera	6 To 7	Diesel	SAE 15W-40
Scorpio	6	Diesel	5W 40, ACEA A3/B4
XUV 500	6	Diesel	5W 40 ACEA A3/B4
Xylo	6	Diesel	5W 40 ACEA A3/B4
Quanta	5	Diesel	SAE 15W-40
Thar	6.5	Diesel	SAE 15W-40
Verito	3.1	Diesel	SAE 5W-30 - ACEA A3/B4
Verito/Nerito Vibe	3.1	Diesel	SAE 15W-40
Ssangyong Rexton	7	Diesel	5W 40, API SM / ACEA A3/B4
Jeep	5.7	Diesel	SAE 15W-40
Logan	4	Diesel	SAE 15W-40
Scorpio	6.5	Diesel	SAE 15W-40
TOYOTA			
Corolla	4	Petrol/Diesel	5W 40, API SM / ACEA A3/B4
Corolla A litis	4.2	Petrol	5W 40, API SM / ACEA A3/B4
Elios/Liva	2.9	Petrol	SAE 5W-30 - ACEA A3/B4
Elios/Liva	3.9	Diesel	SAE 5W-30 - ACEA A3/B4
Fortuner	6.9	Diesel	5W 40, API SM / ACEA A3/B4
Innova	6	Petrol	5W 40, API SM / ACEA A3/B4
Innova	6.8	Diesel	SAE 5W-30 - ACEA A3/B4 or SAE 15W-40
Land Cruiser	4 to 7.5	Petrol	5W 40, API SM / ACEA A3/B4
Camry	4 to 4.2	Petrol	5W 40, API SM / ACEA A3/B4
Prado	6.9	Petrol/Diesel	5W 40, API SM / ACEA A3/B4
Prius	4.2	Petrol	5W 40, API SM / ACEA A3/B4
Qualis	4	Petrol	SAE 5W-30 - ACEA A3/B4
Qualis	4.5	Diesel	SAE 15W-40

TATA MOTORS			
Model	Sump Size	Make	Recommendation
Aria	7.5	Diesel	5W 40, API SM / ACEA A3/B4
Estate	6.7	Diesel	SAE 15W-40
Indica	4	Petrol	10 W 40 - ACEA A3/B4
Indica	5.5	Diesel	SAE 15W-40
Indica Xeta	2.6	Diesel	SAE 15W-40
Indica Xeta	3.7	LPG	SAE 15W-40
Indicab	4	CNG	SAE 15W-40
Indicab	5.5	Diesel	SAE 15W-40
Manza	3.3	Petrol	SAE 5W-30 - ACEA A3/B4
Marina	4	Diesel	SAE 15W-40
NANO	2.5	Petrol	10W40 - ACEA A3/B4
Safari Storm	7.5	Diesel	SAE 15W-40
Safari	7.5	Diesel	SAE 15W-40
Sierra	6.7	Diesel	SAE 15W-40
Spacio	5.5	Diesel	SAE 15W-40
Sumo Grande	7.5	Diesel	SAE 15W-40
Sumo Vitta	7.5	Diesel	SAE 15W-40
Xenon	7.7	Diesel	5W 40, API SM / ACEA A3/B4
Sumo	6.8	Diesel	SAE 15W-40
Indica D'car	5.5	Diesel	SAE 15W-40
HONDA			
Amaze	4.5	Diesel	SAE 15W-40
Amaze	3.6	Petrol	SAE 5W-30
Accord	4.5	Petrol	5W 40, ACEA A3/B4
Brio	3.6	Petrol	SAE 5W-30
Civic	4.5	Petrol	5W 40, ACEA A3/B4
CRV	4.5	Petrol	5W 40, ACEA A3/B4
Jazz	3.7	Petrol	5W 40, ACEA A3/B4
City	3.6	Petrol	5W 40, ACEA A3/B4

\* Oil recommended at Wuerth Lubricants is only indicative purposes based on technical specifications of vehicles manufactured. Please refer to vehicle manufacture service manual for exact specifications.

# WUERTH OIL RECOMMENDATION

FORD			
Model	Sump Size	Make	Recommendation
Figo	4.1	Petrol	SAE 5W-30
Figo	3.9	Diesel	SAE 15W-40
Fiesta	4.5	Petrol	SAE 5W-30
Fiesta	4	Diesel	5W 40,ACEA A3/B4
Eco Sport	4	Petrol	5W 40,ACEA A3/B4
Eco Sport	4	Diesel	5W 40,ACEA A3/B4
Endeavour	6.6	Petrol/Diesel	5W 40,ACEA A3/B4
HYUNDAI			
Accent	3.3	LPG	SAE 15W-40
Accent	3.3	Petrol	SAE 5W-30
Elantra	3.9	Petrol	5W 40,ACEA A3/B4
Elantra	5.9	Diesel	5W 40,ACEA A3/B4
i10	3.1	Petrol	5W 40,ACEA A3/B4
i10	3.1	LPG	SAE 10W-40
Eon	2.5	LPG	SAE 10W-40
Eon	2.5	Petrol	SAE 10W-40
i20	3.6	Petrol	5W 40,ACEA A3/B4
i20	5.3	Diesel	5W 40,ACEA A3/B4
Sonata	4.3 to 4.5	Petrol	5W 40,ACEA A3/B4
Sanfro	3.1	Petrol	SAE 10W-40
Sanfro	3.1	LPG	SAE 10W-40
Tuscan	5.9	Petrol	5W 40,API SM/ACEA A3/B4
Terracan	4.4	Petrol	5W 40,API SM/ACEA A3/B4
Terracan	7.1	Diesel	5W 40,API SM/ACEA A3/B4
Verna	3.3	Petrol	5W 40,API SM/ACEA A3/B4
Verna	5.3	Diesel	5W 40,API SM/ACEA A3/B4
GETZ	5.3	Petrol	SAE 5W-30
GETZ	5.3	Diesel	SAE 15W-40
Santa Fe	4.3 to 5.7	Petrol	5W 40,API SM/ACEA A3/B4
Santa Fe	5.9	Diesel	5W 40,API SM/ACEA A3/B4

FIAT			
Model	Sump Size	Make	Recommendation
Punto	3.2	Petrol	5W 40,API SM/ACEA A3/B4
Punto	3.2	Diesel	5W 40,API SM/ACEA A3/B4
Linea	3.2	Petrol	5W 40,API SM/ACEA A3/B4
Linea	3.2	Diesel	5W 40,API SM/ACEA A3/B4
MARUTI SUZUKI			
A Star	2.9	Petrol	SAE 10W-40/ SAE 20W50
Alto	2.7	Petrol	SAE 20W-50/ SAE 10W40
Alto K10	2.7	Petrol	SAE 5W-30/ SAE 10W40
Alto 800	2.7	CNG	SAE 10W-40
Eeco	5.3	CNG	SAE 10W-40
Eeco	5.3	Petrol	SAE 5W-30
Eriga	3.1	CNG	SAE 10W-40/ SAE 20W50
Eriga	3.1	Petrol	SAE 5W-30
Eriga	3.1	Diesel	5W 40,ACEA A3/B4
Esteem	3.3	Petrol	SAE 5W-30
Esteem	4.7	Diesel	SAE 15W-40
Grand Vitara	4.8	Petrol	5W 40,ACEA A3/B4
Gypsy	4.2	Petrol	SAE 5W-30
Kizashi	3.3	Petrol	5W 40,ACEA A3/B4
Swift	3.1	Diesel	5W 40,ACEA A3/B4
Swift	3.1	Petrol	5W 40,ACEA A3/B4
Swift Dzire	3.1	Diesel	5W 40,ACEA A3/B4
Swift Dzire	3.7	CNG	SAE 10W-40
Wagon R	3.7	Petrol	SAE 5W-30/ SAE 10W40
Wagon R	2.7	Petrol	SAE 5W-30/ SAE 10W40/ SAE 20W50

\* Oil recommended at Wuerth Lubricants is only indicative purposes based on technical specifications of vehicles manufactured. Please refer to vehicle manufacture service manual for exact specifications.

# WUERTH OIL RECOMMENDATION

MARUTI SUZUKI			
Model	Sump Size	Make	Recommendation
Omni	3.2	Petrol	SAE 20W-50/ SAE 10W-40
Ritz	3.1	Diesel	SAE400
Ritz	4.3	CNG	SAE400
SK4	4.3	Petrol	5W 40 ACEA A3/B4
SK4	3.1	Diesel	5W 40 ACEA A3/B4
SK4	4.3	CNG	SAE400
Zen	4.3	CNG	SAE400
Zen	4.3	Petrol	SAE 5W-30
AUDI			
A4	4.5 to 5	Petrol/Diesel	5W 40 ACEA A3/B4
A6	6.5	Petrol/Diesel	5W 40 ACEA A3/B4
A8	8.5	Petrol/Diesel	5W 40 ACEA A3/B4
Q5	5	Petrol/Diesel	5W 40 ACEA A3/B4
Q7	9.5	Petrol/Diesel	5W 40 ACEA A3/B4
R8	8.5	Petrol/Diesel	5W 40 ACEA A3/B4
TT	4.5	Petrol/Diesel	5W 40 ACEA A3/B4
BMW			
3 SERIES	5.2	Petrol/Diesel	0W 40 ACEA A5/B5
5 SERIES	6.5	Petrol/Diesel	0W 40 ACEA A5/B5
6 SERIES	7.7	Petrol/Diesel	0W 40 ACEA A5/B5
7 SERIES	7.2	Petrol	0W 40 ACEA A5/B5
Grand Turismo	7.2	Diesel	0W 40 ACEA A5/B5
M3	6.5 to 8	Petrol/Diesel	0W 40 ACEA A5/B5
M5	7.5 to 8	Petrol/Diesel	0W 40 ACEA A5/B5
X1	6	Petrol/Diesel	0W 40 ACEA A5/B5
X3	5.2	Diesel	0W 40 ACEA A5/B5
X5	7.5 to 8	Petrol/Diesel	0W 40 ACEA A5/B5
X6	7.2	Petrol/Diesel	0W 40 ACEA A5/B5
X4	8	Petrol	0W 40 ACEA A5/B5

SKODA			
Model	Sump Size	Make	Recommendation
Fabia	4	Petrol	5W 40 API SM I ACEA A3/B4
Fabia	4	Diesel	5W 40 API SM I ACEA A3/B4
Laura	4.3	Petrol/Diesel	5W 40 API SM I ACEA A3/B4
Octavia	4.5	Petrol/Diesel	5W 40 API SM I ACEA A3/B4
Superb	4	Petrol/Diesel	5W 40 API SM I ACEA A3/B4
MERCEDES BENZ			
C-Class	5.5 to 8.5	Petrol/Diesel	0W 40 ACEA A5/B5, MB 229.5
CLs-Class	9	Petrol	0W 40 ACEA A5/B5, MB 229.5
E-Class	5.5 to 8.5	Petrol	0W 40 ACEA A5/B5, MB 229.5
GL-Class	8.5 to 11.5	Diesel	0W 40 ACEA A5/B5, MB 229.5
S-Class	6.5 to 9	Petrol/Diesel	0W 40 ACEA A5/B5, MB 229.5
SL/SLs/AMG	8 to 8.5	Petrol	0W 40 ACEA A5/B5, MB 229.5
SLk-Class	5.5 to 8	Petrol	0W 40 ACEA A5/B5, MB 229.5
VOLVO			
XC 60	5.9	Diesel	5W 40 ACEA A3/B4
XC 90	5.9	Diesel	5W 40 ACEA A3/B4
VOLKSWAGEN			
Polo	4.3	Petrol	5W 40 ACEA A3/B4
Polo	4	Diesel	5W 40 ACEA A3/B4
Vento	4.3	Petrol/Diesel	5W 40 ACEA A3/B4
Beetle	3.2 To 4.5	Petrol	5W 40 ACEA A3/B4
Beetle	4.3 to 4.5	Diesel	5W 40 ACEA A3/B4
Jetta	3.2 to 4.6	Petrol	5W 40 ACEA A3/B4
Jetta	3.8 to 4.3	Diesel	5W 40 ACEA A3/B4
Passat	4.6	Petrol	5W 40 ACEA A3/B4
Passat	3.8 to 4.3	Diesel	5W 40 ACEA A3/B4
Touareg	5	Diesel	5W 40 ACEA A3/B4

\* Oil recommended at Wuerth Lubricants is only indicative purposes based on technical specifications of vehicles manufactured. Please refer to vehicle manufacture service manual for exact specifications.

# WUERTH OIL RECOMMENDATION

PORSCHÉ			
Model	Sump Size	Make	Recommendation
911	9	Petrol	0W 40 ACEA A5/B5
Boxster	7	Petrol	0W 40 ACEA A5/B5
Cayenne	7	Petrol	0W 40 ACEA A5/B5
Cayman	9	Petrol	0W 40 ACEA A5/B5
Panamera	7	Petrol	0W 40 ACEA A5/B5
FERRARI			
458 Italia	10.6	Petrol	0W 40 ACEA A5/B5
California	8.3	Petrol	0W 40 ACEA A5/B5
FF	8 TO 10	Petrol	0W 40 ACEA A5/B5
LAND ROVER			
Discovery 4	6	Diesel	0W 40 ACEA A5/B5
Freelander 2	6	Diesel	0W 40 ACEA A5/B5
Range Rover	10	Diesel	0W 40 ACEA A5/B5
Range Rover Evoque	6	Petrol/Diesel	0W 40 ACEA A5/B5
Range Rover Sport	10	Petrol	0W 40 ACEA A5/B5
Range Rover Sport	6 to 10	Diesel	0W 40 ACEA A5/B5
JAGUAR			
XK/XL	10.3	Petrol	0W 40 ACEA A5/B5
XK/XI	10.3	Diesel	0W 40 ACEA A5/B5
XKR	10.1	Petrol	0W 40 ACEA A5/B5
RENAULT			
Pulse/Scala	3	Petrol	5W 40 ACEA A3/B4
Duster	4.5	Petrol	5W 40 ACEA A3/B4
Pulse/Scala	4.5	Diesel	5W 40 ACEA A3/B4
Duster/Fluence/Koleos	4.5	Diesel	5W 40 ACEA A3/B4

MITSUBISHI			
Model	Sump Size	Make	Recommendation
Cedia	3.5	Petrol	5W 40 ACEA A3/B4
Evolution X	5 to 5.6	Petrol	5W 40 ACEA A3/B4
Lancer	3.5 to 4.8	Diesel	5W 40 ACEA A3/B4
Lancer	4.6	Petrol	5W 40 ACEA A3/B4
monter	10	Diesel	5W 40 ACEA A3/B4
Outlander	4.6	Petrol	5W 40 ACEA A3/B4
Pajero	7.8	Diesel	5W 40 ACEA A3/B4
NISSAN			
Micra	3	Petrol	SAE 5W30- ACEA A3/B4
Sunny	3	Diesel	SAE 15W-40
Sunny	2.8 to 3	Petrol	5W 40 ACEA A3/B4
Sunny	4.5	Diesel	5W 40 ACEA A3/B4
Teana	5.8	Petrol	5W 40 ACEA A3/B4
X-trail	5.2 to 7.4	Diesel	5W 40 ACEA A3/B4
CHEVROLET			
Spark	3.8	Petrol	10W40 ACEA A3/B4
Spark	3.8	LPG	10W40 ACEA A3/B4
Beat	3.8	Petrol	10W40 ACEA A3/B4
Beat	3.8	Diesel/LPG	SAE 15W-40
Sail	3.7	Petrol	5W 40 API SM I ACEA A3/B4
Sail	3.7	Diesel	SAE 15W-40
Aveo	3.7	Petrol	5W 40 API SM I ACEA A3/B4
Optra	3.8	Petrol	5W 40 API SN I ACEA A3/B4
Optra	3.8 to 5	Diesel	5W 40 API SM I ACEA A3/B4
Cruze	6.2	Petrol	5W 40 API SM I ACEA A3/B4
Tavera	6	Diesel	SAE 15W-40
Carliva	6.2	Diesel	5W 40 API SM I ACEA A3/B4
Carliva	4.5	Petrol	5W 40 API SM I ACEA A3/B4
Sail UVA	3.75	Petrol	5W 40 API SM I ACEA A3/B4

\* Oil recommended at Wuerth Lubricants is only indicative purposes based on technical specifications of vehicles manufactured.  
Please refer to vehicle manufacture service manual for exact specifications.

# WHAT IS ORSY®?

ORder with a SYstem is a flexible logistic solution that is ideal for goods with a irregular need.

ORSY will enable you to reduce costs optimize your inventory and realize your goal of higher efficiency giving you a overview of your inventory your purchase and point of consumption.



# LUBRICANTS & COOLANTS CATALOGUE

APRIL 2021

## Wuerth India Pvt. Ltd.

### Central Support Centre:

**Mumbai:** No 703/704, WINDFALL, Sahar Plaza Complex,  
Andheri - Kurla Road, J B Nagar, Andheri (East), Mumbai - 400059

### Regional Support Centre:

**Chennai:** No. 156, Doshi Towers, 6A & 6B,  
Poonamallee High Road, Kilpauk, Chennai - 600010

### Regional Support Centre:

**Delhi:** No. 349, Patparganj Industrial Estate  
Delhi - 110092

### Regional Support Centre:

**Kolkata:** Plot No. 1812, PS Srijan Corporate Park,  
GP Block, Sector V, Bidhannagar, Kolkata, West Bengal - 700091

[www.wuerth.in](http://www.wuerth.in)

[info.wuerth@wuerth.in](mailto:info.wuerth@wuerth.in)

Toll Free: 1800 102 5061

Follow us on   



**Wuerth India eSHOP**

**Register Now**

@ [www.wuerth.in](http://www.wuerth.in)



WUERTH APP

